

# Sensor chip and photoelectric conversion apparatus using the same

**Patent number:** EP0382540

**Publication date:** 1990-08-16

**Inventor:** NAKAMURA KENICHI KOTOBUKIHAITS; KOIDE  
YOSHIO CANON DAINI HONAT

**Applicant:** CANON KK (JP)

**Classification:**

- **International:** G11C19/00; H04N1/18; H04N3/15

- **European:** G11C19/00; H04N1/193; H04N1/193B; H04N3/15G;  
H04N3/15J

**Application number:** EP19900301355 19900208

**Priority number(s):** JP19890030015 19890210; JP19890030016 19890210;  
JP19890030018 19890210

**Also published as:**



EP0382540 (A3)

EP0382540 (B1)

**Cited documents:**



EP0260956

GB2160058


EP0292253

JP61214564

[Report a data error here](#)

## Abstract of EP0382540

A sensor chip includes output signal lines for outputting signals outside the sensor chip from light-receiving elements of the sensor chip, a switch for connecting/disconnecting the output signal lines, and a controller for closing the switch only for a duration including a time interval in which signals are output outside the sensor chip from the light-receiving elements, and opening the switch for a duration except for the duration. A multichip photoelectric conversion apparatus in which a plurality of sensor chips each having a plurality of light-receiving elements are arranged, includes output signal lines, connected to a common signal line, for outputting signals outside the sensor chip from light-receiving elements of the sensor chip, a switch, provided for each of the sensor chips, for connecting/disconnecting the output signal lines, and a controller, provided in each of the sensor chips, for closing the switch only for a duration including a time interval in which signals are output outside the sensor chip from the light-receiving elements, and opening the switch for a duration except for the duration.



Data supplied from the [esp@cenet](mailto:esp@cenet) database - Worldwide